

Single Pass Efficiency in a Compact Size

Digital Inkjet Color Printer
Swift Color Label
SCL-4000D / SCL-4000P



Features

- High speed. SCL-4000D: 7.9ips (200mm/sec)
SCL-4000P: 5.9ips (150mm/sec)
- High quality. 1200dpi
- Multi-color printing (4 color/BK, C, M, Y)
- Single-pass printhead architecture
- Desktop, compact and lightweight

Versatile Applications

Shipping case marks, address stickers, baggage tags, barcodes, cosmetic, health care product, prescription medicine packaging, gourmet food and bottle labels and MORE!

Product Specifications

SCL-4000D / SCL-4000P		
Printer Model	SCL-4000D	SCL-4000P
Print Technology	Ink jet (single pass printing)	Ink jet (single pass printing)
Type of the Ink	Dye based ink	Pigment based ink
Print Color	4 color (Bk, C, M, Y)	4 color (Bk, C, M, Y)
Weight	52.91 lbs. (24kg) excluding head and ink cartridge	52.91 lbs. (24kg) excluding head and ink cartridge
Dimensions (w X d X h)	15.9 (W) x x 22.44 x 15.51 inches (386 x 570 x 394 mm)	15.9 (W) x x 22.44 x 15.51 inches (386 x 570 x 394 mm)
Print Resolution	1200x1200dpi	1200x1200dpi
	# of Print Heads	4
	Print Width	4.17 inches or less (105.9 mm or less)
Print Speed	1.96 - 7.87 inches (50 - 200 mm) / sec	1.96 - 5.90 inches (50 - 180 mm) / sec
Print Area	Max. Width	4.17 inches or less (105.9 mm or less)
	Length	0.11 - 15.62 inches (3.0 - 397.0 mm)
Margins	Top/Bottom	0.05 inches (1.5mm)
	Left/Right	0.010 inches (2.7mm) including liner
Type of the Media	Type of Paper	Exclusive roll paper (label, tag) Exclusive fanfold paper
	TOF	Label/gap, Label/mark, Tagmark, Continuous paper (without TOF)
Media Size	Width	1 - 4.72 inches (25.4-120mm)
	Length	0.23 - 15.74 inches (6.0 - 400 mm)
	Thickness	145 - 255 µm (label/tag)
Media Roll Size	Outer diameter: Ø7.87 inches (200mm) and less. Core diameter: Ø3.00 ± 0.03 INCHES (76.2 ± 1.0 mm)	Outer diameter: Ø7.87 inches (200mm) and less. Core diameter: Ø3.00 ± 0.03 INCHES (76.2 ± 1.0 mm)
Interface	Data Transmission	USB2.0 Hi-speed function Giga Bit Ethernet
	Extension	RS232C 1, RS232C 2 interface for option
OS		WinXP, Vista, Win7
Power Supply		AC 100-240V, 50-60Hz
Max. Power Consumption		233W (Printer only)
Operating Environment (Temperature/Humidity)		59°F (15°C) 10% - 86°F (30°C) 80%
Ink Cartridges	Color	Bk/C/M/Y
	Capacity	240ml for each color
Option		Auto cutter


* Specifications subject to change without notice




Simple ink cartridge replacement



Easy label roll replacement



Print module available for other systems, production lines and kiosks



Single-pass printing SCL-4000 Serial printing

Ahearn & Soper Inc.
proVisionWMS

100 Woodbine Downs Blvd
Toronto, ON M9W 5S6
Tel: 800-263-4258 / 416-675-3999
Québec: 800-361-9584
Western Canada: 800-468-7025

swiftcolorTM
www.swiftcolor.com
info@swiftcolor.com

KG[®]
digital
SOLUTIONS

Japan: 2-1, Shibaura 1-Chome, Minato-Ku, Tokyo 105-8005 Japan
US: 100 Randolph Road, Somerset, New Jersey 08873, USA
Europe: Oststrasse 34, D-40211 Dusseldorf, Germany
Asia: 25th Floor, Thaniya Plaza Bldg., 52 Silom Road, Suriyawongse, Bangkok 10500, Thailand