



The Zenius printer is designed for single sided printing of a very large variety of plastic cards. Zenius generates color or monochrome cards, individually or in small runs, with top quality results. Zenius is a user-friendly, compact and cost-effective solution for delivering your personalized cards.

FLEXIBILITY

- With Zenius, you can choose to insert your cards individually or with the automatic feeder.
- The «Expert» version of Zenius features combinable encoding functions: magnetic encoding, contact and contactless chips.
 It takes just a few minutes to install these modules!

EASE OF USE

- With the Evolis Premium Suite® software, you can receive notifications and easily control the printer from your computer.
- Evolis High Trust® ribbons are easy to install and automatically recognized and set by the printer.

SMALL FOOTPRINT

- Hardly larger than a standard sheet of paper, Zenius fits perfectly into any environment, be it the office or a customer service counter.
- Zenius is an eco-designed printer: very efficient sleep mode and low energy consumption.







MAIN FEATURES / Full technical specifications on www.evolis.com

GENERAL FEATURES

- Direct-to-card dye-sublimation/Resin thermal transfer
- · Single-sided printing, edge-to-edge
- 300 dpi print head (11.8 dots/mm)
- 16 million colors
- 16 MB memory (RAM), 32 MB for the Expert version
- Colors available: fire red & grey brown

PRINTING PERFORMANCES

- Color (YMCKO): 120 150 cards/hour¹
- Monochrome: 400 500 cards/hour

INTERFACES

- USB (1.0, 1.1, 2.0, 3.0), cable supplied
- Ethernet TCP-IP 10BaseT, 100BaseT (Traffic Led) on the Expert version

CARD MANAGEMENT AND SPECIFICATIONS

- · Automatic or manual feeding
- Feeder capacity: 50 cards (0.76 mm 30 mil)
- Output hopper capacity: 20 cards (0.76 mm 30 mil)
- Card thickness: 0.25 to 0.76 mm (10 to 30 mil), gauge adjustment
- Card types: PVC cards, composite PVC cards, PET cards, ABS cards¹, special varnished cards¹
- Card format: ISO CR80 ISO 7810 (53.98 mm x 85.60 mm)

ADDITIONAL ENCODING MODULES

- Available modules on the Expert version:
- Magnetic stripe encoder ISO 7811 HiCo/LoCo, JIS2
- Magnetic stripe encoder ISO 7811 HICO/LOCO, JIS2 Smart contact station ISO 7816-2 Contact smart card encoder PC/SC, EMV 2000-1 Contactless smart card encoder ISO 14443A, B, ISO15693, MIFARE, DESFire, HID iCLASS
- Other specific encoders upon request
- Internal USB ports
- · Options can be combined
- Factory-installed or installed on site

SAFETY

- Support for Kensington® security lock
- · Data encryption for magnetic encoding

- Printer LEDs
- Graphical notifications from the printer²: cleaning alerts, empty/low level ribbon and card alerts, etc.

EVOLIS HIGH TRUST® RIBBONS

To maximize the quality and durability of printed cards, the lifespan of the print head and the overall printer reliability, use Evolis High Trust® ribbons.

- · Automatic identification and setting
- Delivered in a drop-in cassette for easy handling
- · Ribbon saver for monochrome printing

List of ribbons available on www.evolis.com

SOFTWARE

- Delivered with Evolis Premium Suite® for Windows®:
 - Printer driver
 - Evolis Print Center for administration and settings
- Evolis Printer Manager for graphical notification
- 24/7 online support
- Compatible with Windows® (32/64 bits): XP SP3, Vista,
- Delivered with cardPresso XXS Lite for designing and
- Internal database up to 50 records
 Windows® (from XP onwards) and Mac OS X
- Delivered with a driver for Mac OS X (from 10.5 onwards)
- · Linux OS upon request
- Evolis Premium SDK for remote supervision of the printer, while facilitating and speeding up integration into IT systems

ECO-FRIENDLY DESIGN, CERTIFICATIONS AND STATEMENT OF COMPLIANCE

- Standby, sleep modes & reduced energy consumption
- CE, FCC, IEC, VCCI, CCC, KC, BIS, EAC

SIZE AND WEIGHT

- Size (H x W x D): 195 x 205 x 315 mm (7.68" x 8.07" x 12.4")
- Weight: 3.3 kg (7.3 lbs)

- 2-year warranty (printer and print head)4
- Warranty extension available as an option

1 Under specific conditions / 2 Depends on the Windows® version / 3 Requires the .net 4.0 client profile version 4 Warranty subject to observance of specific conditions and use of Evolis High Trust® ribbons







Sales & Service Offices Across Canada

TORONTO: ON | 416.675.3999 - 800.263.4258 CAMBRIDGE: ON | 800.461.2898 OTTAWA: ON | 800.267.4267 MONTREAL: QC | 800.361.9584 CALGARY: AB | 800.468.7025 EDMONTON: AB | 800.468.7025

VANCOUVER: BC | 800.468.7025

US & CANADA

Evolis, Rising Sun Mills, 188 Valley St., Suite 421 - Providence, RI 02909 T: 401-751-5483 - F: 954-777-9267 - evolisnortham@evolis.com

HQ | EUROPE - MIDDLE-EAST - AFRICA - Angers - info@evolis.com

LATIN AMERICA - Miami - evolislatam@evolis.com ASIA-PACIFIC - Singapore - evolisasia@evolis.com CHINA - Shanghai - evolischina@evolis.com JAPAN - Tokyo - evolisjapan@evolis.com

INDIA - Mumbai - evolisindia@evolis.com

©2016 Evolis. All rights reserved. Actual product(s) may differ from information stated in this document. All specifications or pictures are subject to change without prior notice. All trademarks mentioned herein belong to their respective owners. Pictures: Olivier Calvez. 10/2016. KB-ZEN1-064-ENG-US Rev D2