

LD-100 & LD-200

Heavy-Duty Label Dispensers (Page 1 of 2)



Model – S For very small or unusual shape labels.

The LD-100-S uses a unique concept that solves dispensing problems for very small and unusual labels that most competitors' dispensers can't handle. This Dispenser cleverly strips the label from the label web and then gently places it back on the web ready for the operator to pick at the front of the machine. The LD-100-S can continuously advance labels at the rate you choose or advance labels only when the included Foot Switch is pressed. Add the

Optional **Label Roll Bracket LRB-12** (see next page) to allow use of label supply rolls up to 12" in diameter.

MODEL	DESCRIPTION	LABEL WIDTH	LABEL LENGTH	ROLL DIA.
LD-100-S	Label Dispenser with continuously variable Speed Control and Foot Switch. Ideal for production lines and very small or transparent labels. The optional LD-FLANGES can also be used with the LD-100S..	4.5" max. (114-mm) No minimum width.	Not limited	8.6" max. (220-mm) Core I.D. 1.5" to 3"

Model – RS *With advanced Reflective Sensor* – Simple, Reliable and Convenient!

The Models LD-100-RS & LD-200-RS use the latest opto-electronic technology. There is just one simple adjustment for label length. A special Reflective Sensor sits below the label to reliably and accurately sense the leading edge of your label. As you pick up a label the next one is automatically advanced. This modern design presents the label at the front of the machine, providing optimum convenience for both left-handed and right-handed operators. A "HIGH-LOW" Speed switch allows adjustment for label length or operator preference. There are no mechanical position switches to cause adjustment or operational problems. The new Stainless Steel Models are ideal for food industry and pharmaceutical applications.

KEY FEATURES



- Easy loading.
- Easy access to dispensed labels.
- Works with labels as short as 1/4".
- Small footprint 9" x 9".
- Equally convenient for right and left handed operators.
- "HIGH-LOW" Speed Switch.



New! Stainless-steel LD-100-RS-SS

LD-100-RS with Optional Flanges and Counter

MODEL	DESCRIPTION	LABEL WIDTH	LABEL LENGTH	ROLL DIA.
LD-100-RS	Label Dispenser automatically advances the next label ready to pick. Fast label loading. Quick and convenient operation. Not for transparent labels.	1/2" to 4.5" (25- to 114-mm)	0.25" to 6" or more (6- to 150-mm)	8.6" max. (220-mm). Core I.D. 1.5" to 3"
LD-200-RS	Same features as LD-100RS, but with wider label capacity .	1/2" to 6.5" (25- to 165-mm)		
LD-100-RS-SS	<i>New!</i> LD-100-RS with sleek Stainless-Steel chassis and sealed Stainless-Steel cover. Ideal for food industry or pharmaceutical applications.	1/2" to 4.5" (25- to 114-mm)		
LD-200-RS-SS	<i>New!</i> Sleek Stainless-Steel LD-200-RS	1/2" to 6.5" (25- to 165-mm)		

The World's Leading Manufacturer of Label Dispensers, Rewinders, Unwinders, Slitters & Core Chucks
LABELMATE LLC, 12A Sunset Way, Henderson, NV 89014-2002 USA

Toll-Free (877) 833-7149 (702) 435-8535 FAX (702) 435-8536

www.labelmate.com

E-mail: info@labelmate.com

LABELMATE Europe - Brussels, Belgium

Heavy-Duty Label Dispensers (Page 2 of 2)

Model – T For Transparent, Semi-Transparent or Opaque Labels

The **LD-100-T** & **LD-200-T** Label Dispensers advance the state-of-the-art of label dispensing with their ability to dispense virtually any type of label: opaque, semi-transparent, or even *completely transparent!* Using LABELMATE's patented sensor technology, the dispensers reliably peel your label from its backing and present it ready to pick. As you pick a label from the Dispenser, the next one is automatically advanced. A "HIGH-LOW" Speed Switch and an adjustable Ruggedized Sensor to match label length and solve label curling problems are standard features. Add the Optional Label Roll Bracket **LRB-12** to allow use of label supply rolls up to 12" in diameter.



LD-100-T / LD-200-T



with Optional LDC-1 Counter & LD-FLANGES



A Ruggedized Label Sensor is now standard on the LD-100-T & LD-200-T.

MODEL	DESCRIPTION	LABEL WIDTH	LABEL LENGTH	ROLL DIA.
LD-100-T	Label Dispenser automatically advances the next label ready to pick. Fast label loading. Quick and convenient operation! For transparent or opaque labels. <i>Now includes Ruggedized Label Sensor as standard.</i>	1/2" to 4.5" max. (25- to 114-mm)	0.5" to virtually unlimited.	8.6" max. (220-mm).
LD-200-T	Same features as LD-100-T, with Wider Label Capacity.	1/2" to 6.5" max. (25- to 165-mm)		Core I.D. 1.5" to 3"

ORDER	LABEL DISPENSER OPTIONS
LDC-1	Optional Label Counter (Factory-installed). Not available for Stainless Steel (-SS) models.
FLANGES- LD	Optional aluminum Flange Plates suggested for use with narrow labels that may have a tendency to telescope or fall off the Core. Set of 2 Flanges. 8.6" (220-mm) in diameter.
LRB-12	<i>New!</i> Optional Label Roll Bracket Extension to allow use of label supply rolls up to 12" (30-cm) in diameter. Includes mounting hardware. Installs in minutes. For LD-100 models only. See photo below.

Rugged, heavy-gauge steel construction will stand up to all-day, every-day use. All Dispensers are backed by LABELMATE's famous **3-Year Parts and Labor Limited Warranty**, assuring you trouble-free performance. Put a new LABELMATE Heavy-Duty Label Dispenser to work for you, today!

All LD Models: Size: HWD Approx. 11x9x9-inches (280x229x229-mm). Weight: 14- to 15-lbs (6.4- to 6.8-kg). Power: 120V 60Hz 40-wa. 220-240V 50-Hz also available at the same price. Specify.



New! Optional **LRB-12** Extension Bracket for LD-100 model Label Dispensers allows use of label roll diameters up to 12".

Free consultation 1-877-833-7149
www.labelmate.com

Specifications are subject to change without notice. DataLD 2006-09

The World's Leading Manufacturer of Label Dispensers, Rewinders, Unwinders, Slitters & Core Chucks
LABELMATE LLC, 12A Sunset Way, Henderson, NV 89014-2002 USA
Toll-Free (877) 833-7149 (702) 435-8535 FAX (702) 435-8536
www.labelmate.com E-mail: info@labelmate.com
 LABELMATE Europe - Brussels, Belgium