



Mobile Thermal Printer



PV4

Mobile 4-inch Thermal Printer



KEY FEATURES AND BENEFITS

- 2 inch color LCD with 80° viewing angle
- Drop resistance of 6-feet
- Fan fold support for mounting
- Belt clip provides mobility for hands-free operation



- Bluetooth, WiFi and USB connectivity
- Extra capacity 6700 mAh battery
- Water resistant and dust proof (IP54)
- Built-in dispenser
- 2.6 inch OD for maximum labels per roll



Made for iPhone | iPad | iPod

www.satoamerica.com/PV4

GENERAL SPECIFICATIONS / PV4

PRODUCT SPECIFICATIONS			
Print Resolution		203 dpi	
Print Speed		5 ips	
Print Area	Max Width	4.1" (104mm)	
	Max Length	15.7" (400mm)	
Media Size (with liner)	Width	4.4" (112mm)	
	Length	15.7" (400mm)	

PRINTING SPECIFICATIONS		CONNECTIVITY		BARCODE SYMBOLOGIES	
Method		Standard		Barcodes	

Direct Thermal
Mode
Continuous, Tear-off, Dispenser

USB 2.0 (Type C connector), Bluetooth® Ver. 5.0 LE
Optional WiFi
IEEE 802.11 a/b/g/n (Infrastructure, Ad-hoc, Soft AP)

Linear
Codebar, Code 11, Code 39, Code 93, Code 128, EAN-13, EAN-8, Industrial 2-of-5, Interleaved 2-of-5, Logmars, MSI, Plessey, Postnet, GS1 DataBar (RSS-14), Standard 2-of-5, UPC/EAN Extensions, UPC-A, UPC-E, IMB

MEDIA SPECIFICATIONS	
Sensor Type	

Gap, Black Mark
Media Type

MEMORY & PROCESSING	
Printer Memory	

256MB Flash, 128MB SDRAM
User Downloadable Fonts, Videos, Graphics or Format
Maximum 5MB

2D Symboologies
Aztec, Codablock, Code 49, Composite Symboologies, Data Matrix, MaxiCode, MicroPDF417, PDF417, QR code, TLC 39

Roll (face-out), Fan-fold Label, Receipt
Media

Thickness (Label & Liner)
0.003" - 0.006" (0.07 - 0.15mm)

USER FRIENDLY SUPPORT TOOLS	
Large Status LED	

Red: Charging
Green: Fully Charged
Red Blinking: Error, Replace, or Reinstall Battery

OPERATING CHARACTERISTICS	
Electrical Requirements	

AC 100 V to 240 V (90 ~ 264 Vac)
Output voltage: 9 Vdc (9 ~ 9.55 Vdc)

Up to 2.60" (66mm)
Inner Roll Diameter

0.75" (19mm), 0.5" (12mm)
Wind

Audible Alerts
Buzzer

Battery
7.2V Li-ion, 6,700 mAh 48 Wh

Face-out
SATO Genuine Consumables

For maximum print quality and optimum use, SATO recommends the use of SATO genuine consumables.

Self Diagnosis
Cover Open, Label Presence

Standards & Agency Approvals
Please contact SATO regarding agency approvals in your region.

FONT SPECIFICATIONS	
Internal Fonts	

33 Bitmap and 2 Scalable Fonts, Multi-national Language Support for Major Latin, Pan European and Asian Languages, Single and Double Byte Fonts

Display Panel
2" Color LCD (240 x 320 pixels)

Environment
Operating
5 - 122°F (-15 - 50°C) / 10 - 80% RH (without condensation)

Emulation
SLCS, BPL-Z™, BPL-C™

Storage
-22 - 140°F (-30 - 60°C) / 10 - 90% RH (without condensation)

OPTIONS	
Included	

Lithium-ion Battery, Belt Clip
Optional
1 Bay Charger, 4 Bay Charger, Belt Clip, Lithium-ion Battery, AC Adapter

PHYSICAL CHARACTERISTICS	
Dimensions	

7.3" L x 6.2" W x 3.2" H (186mm x 158mm x 82mm)
Weight

2.4 lbs (1094g) (including battery, excluding media)
Battery Weight of 0.5 lbs (235g)

Construction
Polycarbonate Body and Rubber Overmolding

Durability
Withstands Multiple 6' (1.8m) Drop Impacts
Water and Dust-proof IP54 (printer only)

MISCELLANEOUS	
Functions - Useful Features	

iOS, Android and Windows SDKs, Configuration Tools, Built-in Dispenser, Virtual COM for USB, Label Design Software, Mobile Printing App, Visual Battery Status
--

SATO AMERICA CORPORATE

10350-A Nations Ford Rd
Charlotte, NC 28273
Phone: (704) 644-1650
sales-sal@sato-global.com

LABEL MANUFACTURING, SERVICE & SALES

UNITED STATES MEXICO CENTRAL AMERICA
CANADA CARIBBEAN

www.satoamerica.com/PV4